



SECTION A-A

GENERAL TOLERANCES FOR DIMENSIONS AND FORM POSITION (Ref. ISO 2768 sk)		DEVIATIONS FOR RADI AND CHAMFERS RANGE OF NOMINAL DIMENSIONS		DEVIATIONS FOR GEOMETRY		NAME	DATE	TUFF PLAST PUNE PVT. LTD.	
DEVIATIONS FOR LINEAR DIMENSIONS		DEVIATIONS FOR ANGULAR DIMENSIONS		ABOVE	UPTO	MANOJ	24/12/21	DATE	REVISION
RANGE OF NOMINAL DIMENSIONS	ABOVE	RANGE OF NOMINAL DIMENSIONS	ABOVE	UPTO	UPTO	MILLIND	23/12/21	MODEL NAME	
0.5 3 6 30 120 315 1000 2000	±0.1	0.5 3 6 30 120	±0.2	10 30 100 300 1000 3000	0.8	KARVE <td>24/12/21 <td>38T-5M pulley-insert</td> <td></td> </td>	24/12/21 <td>38T-5M pulley-insert</td> <td></td>	38T-5M pulley-insert	
3 6 30 120 315 1000 2000 4000	±0.2	TOL. ±0.2, ±0.5, ±1, ±2	IF IN DOUBT. ASK	0.2 0.4 0.6 0.8 1	1	MATERIAL:		DWG NO./PART NO.	
±0.1 ±0.1 ±0.2 ±0.3 ±0.5 ±0.8 ±1.2 ±2	±1°	±1°	±20'	0.2 0.2 0.2 0.2 0.2 0.2	0.2	WEIGHT: Grom		38T-5M pulley-insert	
			±10'	↗	↗	DO NOT SCALE			SHEET 1 OF 2