



SECTION A-A

GENERAL TOLERANCE'S FOR DIMENSIONS AND FORM POSITION (Ref. ISO 2768 sk)

	DEVIATIONS FOR LINEAR DIMENSIONS				DEVIATIONS FOR ANGULAR DIMENSIONS								
	RANGE OF NOMINAL DIMENSIONS				RANGE OF NOMINAL DIMENSIONS								
ABOVE	0.5	3	6	30	120	315	1000	2000	ABOVE	-	10	50	120
UPTO	3	6	30	120	315	1000	2000	4000	UPTO	10	50	120	-
TOL.	±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	TOL.	±1°	±30'	±20'	±10'

DEVIATIONS FOR RADI AND CHAMFERS

RANGE OF NOMINAL DIMENSIONS			
0.5	3	6	30
3	6	30	120
TOL. ±0.2 ±0.5 ±1 ±2			
IF IN DOUBT. ASK			

DEVIATIONS FOR GEOMETRY

	ABOVE	10	30	100	300	1000
—	10	30	100	300	1000	3000
—∇	0.05	0.1	0.2	0.4	0.6	0.8
⊥	0.4	0.4	0.4	0.6	0.8	1
≡	0.6	0.6	0.6	0.6	0.8	1
/	0.2	0.2	0.2	0.2	0.2	0.2



MODEL NAME:- 40L PULLEY-INSERT
DWG NO.:- L-040-B-PRT-H-04.22

DATE: _____ REVISION: _____

PROPRIETARY & CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TUFFPLAST ANY REPRODUCTION IN PART IS PROHIBITED.

SHEET 1 OF 1
DO NOT SCALE

DRAWN: MANOJ 4/5/22

CHK'D: TUKARAM 4/5/22

APPV'D: MILLIND 4/5/22

MATERIAL: _____

WEIGHT: Gram
A4